

Model: ZC-69DT

ATF Exchanger

- 5-inch large-screen LCD display navigation operation, simple and practical;
- Anti-cracking high-strength and high-microcrystalline panel, impact resistance, high temperature resistance, corrosion resistance, easy to clean;
- Fully automatic identification of the direction of oil in and out / intelligent conversion of the direction of oil in and out of the gearbox;
- Fully automatic intelligent electronic control of high-precision equal exchange of new and old oil;
- Automatic transmission cycle cleaning function;
- Automatic filling, reducing automatic transmission oil function;
- Effectively solve the problem of incomplete manual replacement of gearbox oil;
- A variety of special connectors, suitable for European, American and Asian models.

Technical parameter

- Voltage: DC12V (with car battery cable)
- Maximum power: 150W
- Pressure gauge: 0~1.5Mpa
- Filter Accuracy: 5 μ m
- Fuel Tank: 20L x 2
- Oil pipe: min 2.3 m Oil return pipe: 2.3 m Oil drain pipe: 1.5m
- Equivalent exchange error: \pm 100g
- Relative humidity: <85%
- Working temperature: -10~+40 degree Celsius
- Volume (cm): 69*49*105 Gross Weight: 49kg



Note: The Picture pattern just for references may change

China Office

Dongan Village, Liushi Town, Yueqing City, Zhejiang Province, China
Tel:0086-577-6286870, E-mail:export.labtech@gmail.com

Bangladesh Office

LabTech Engineering
West Monipur, Mirpur-2, Dhaka-1216
E-mail: way2labtech@gmail.com